


# FTR - Flight Test Report / Tandem Trimmer: offen / open

Dieser Prüfbericht darf ohne schriftliche Zustimmung der EAPR nicht, auch nicht auszugsweise, vervielfältigt werden.

Manufacturer	 Skywalk GmbH & Co.KG Windeckstr. 4 D-83250 Marquartstein	Type testing No.	EAPR-GS-0005/13
		Date	16.08.13
Model	Join'T3 S	Location	Schruns
			Achensee



Rev. 2.1 - 13.08.2013  
 EAPR GmbH - Marktstr. 11  
 D-87730 Bad Grönenbach - Germany

Date of testing	Minimum take off weight		Maximum take off weight	
	21.06.13		11.06.13	
Testpilot	Hannes Tschofen		Mike Küng	
Harness	EAPR TE		EAPR TE	
Pilot's take off weight	100 kg		200 kg	

Classification	B
----------------	---



Test-criteria	Minimum take off weight	Evaluation	Maximum take off weight	Evaluation
<b>1. Inflation / take-off - 4.1.1</b>				
Rising behavior	Smooth, easy and constant rising	A	Smooth, easy and constant rising	A
Special take off technique required	No	A	No	A
<b>2. Landing - 4.1.2</b>				
Special landing technique required	No	A	No	A
<b>3. Speeds in straight flight - 4.1.3</b>				
Trim speed more than 30km/h	Yes	A	Yes	A
Speed range using the controls larger than 10km/h	Yes	A	Yes	A
Minimum speed	Less than 25 km/h	A	Less than 25 km/h	A
<b>4. Control movement - 4.1.4</b>				
Max. weight in flight up to 80kg		-		-
Max. weight in flight 80 to 100kg		-		-
Max. weight in flight greater than 100kg	Increasing >65 cm	A	Increasing >65 cm	A
<b>5. Pitch stability exiting accelerated flight - 4.1.5</b>				
Dive forward angle on exit	Dive forward less than 30°	A	Dive forward less than 30°	A
Collapse occurs	No	A	No	A
<b>6. Pitch stability operating controls during accelerated flight - 4.1.6</b>				
Collapse occurs	No	A	No	A
<b>7. Roll stability and damping - 4.1.7</b>				
Oscillations	Reducing	A	Reducing	A
<b>8. Stability in gentle spirals - 4.1.8</b>				
Tendency to return to straight flight	Spontaneous exit	A	Spontaneous exit	A
<b>9. Behaviour in a steeply banked turn - 4.1.9</b>				
Sink rate after two turns	More than 14m/s	B	More than 14m/s	B
<b>10. Symmetric front collapse - 4.1.10</b>				
Entry	Rocking back less than 45°	A	Rocking back less than 45°	A
Recovery	Spontaneous in less than 3 sec	A	Spontaneous in less than 3 sec	A
Dive forward angle on exit	0° - 30°   Keeping course	A	30° - 60°   Keeping course	B
Cascade occurs	No	A	No	A
<b>11. Exiting deep stall (parachutal stall) - 4.1.11</b>				
Deep stall achieved	Yes		Yes	
Recovery	Spontaneous in less than 3 sec	A	Spontaneous in less than 3 sec	A
Dive forward angle on exit	0° - 30°	A	30° - 60°	B
Change of course	Changing course less than 45°	A	Changing course less than 45°	A

Cascade occurs	No	A	No	A					
<b>12. High angle of attack recovery - 4.1.12</b>									
Recovery	Spontaneous in less than 3 sec	A	Spontaneous in less than 3 sec	A					
Cascade occurs	No	A	No	A					
<b>13. Recovery from a developed full stall - 4.1.13</b>									
Dive forward angle on exit	0° - 30°	A	30° - 60°	B					
Collapse	No collapse	A	No collapse	A					
Cascade occurs (other than collapse)	No	A	No	A					
Rocking backward	Less than 45°	A	Less than 45°	A					
Line tension	Most lines tight	A	Most lines tight	A					
<b>14. Asymmetric collapse (trim speed) - 4.1.14</b>									
Change of course until re-inflation	max 50% collapse	< 90°	Dive or roll angle	0° - 15°	A	90° - 180°	Dive or roll angle	15° - 45°	B
Re-inflation behavior		Spontaneous re-inflation		A	Spontaneous re-inflation		A		
Total change of course		Less than 360°		A	Less than 360°		A		
Collapse on the opposite side occurs		No		A	No		A		
Twist occurs		No		A	No		A		
Cascade occurs		No		A	No		A		
Change of course until re-inflation	max 75% collapse	90° - 180°	Dive or roll angle	15° - 45°	B	90° - 180°	Dive or roll angle	15° - 45°	B
Re-inflation behavior		Spontaneous re-inflation		A	Spontaneous re-inflation		A		
Total change of course		Less than 360°		A	Less than 360°		A		
Collapse on the opposite side occurs		No		A	No		A		
Twist occurs		No		A	No		A		
Cascade occurs		No		A	No		A		
<b>15. Directional control with a maintained asymmetric collapse - 4.1.15</b>									
Able to keep course straight	Yes	A	Yes	A					
180° turn away from the collapsed side possible in 10 sec	Yes	A	Yes	A					
Amount of control range between turn and stall or spin	More than 50% of the symmetric control travel	A	More than 50% of the symmetric control travel	A					
<b>16. Trim speed spin tendency - 4.1.16</b>									
Spin occurs	No	A	No	A					
<b>17. Low speed spin tendency - 4.1.17</b>									
Spin occurs	No	A	No	A					
<b>18. Recovery from a developed spin - 4.1.18</b>									
Spin rotation angle after release	Stops spinning in less than 90°	A	Stops spinning in less than 90°	A					
Cascade occurs	No	A	No	A					
<b>19. B-line-stall - 4.1.19</b>									
Change of course before release		NA		NA					
Behaviour before release		NA		NA					
Recovery		NA		NA					
Dive forward angle on exit		NA		NA					
Cascade occurs		NA		NA					
<b>20. Big ears - 4.1.20</b>									
Entry procedure	Special device required	A	Special device required	A					
Behaviour during big ears		A	Stable flight	A					
Recovery	Spontaneous in 3 to 5 sec	B	Spontaneous in less than 3 sec	A					
Dive forward angle on exit	0° - 30°	A	0° bis 30°	A					
<b>22. Behaviour exiting a steep spiral - 4.1.22</b>									
Tendency to return to straight flight	Spontaneous exit	A	Spontaneous exit	A					
Turn angle to recover normal flight	Less than 720°, spontaneous recovery	A	Less than 720°, spontaneous recovery	A					
<b>23. Alternative means of directional control - 4.1.23</b>									
180° turn achievable in 20 sec	Yes	A	Yes	A					
Stall or spin occurs	No	A	No	A					
<b>24. Any other flight procedure and/or configuration described in the user's manual - 4.1.24</b>									
Procedure works as described		NA		NA					
Procedure suitable for novice pilots		NA		NA					
Cascade occurs		NA		NA					
<b>25. Remarks of testpilot:</b>									
	B-Stall lt. Hersteller im Handbuch ausgeschlossen		B-Stall lt. Hersteller im Handbuch ausgeschlossen						
Copyright Ralf Antz 2013									
This Flight Test Report was generated automatically and is valid without signature									